



RZ-RBZ

Reaktori III za detuniranje prigušnice

Tip	Šifra	400 V kvar	Hz	Za kondenzator	In (A)	Gubici L(mH) (W)	Veličina (mm) š x v x d	težina (kg)
400 Vac, 50 Hz, f rezonancija = 189 Hz / p= 7%								
RZ-5-400	[*] P73110.	5	50	CLZ-FP-46/6,25	7,2	7.66 26	155x165x92	4,00
RZ-6,25-400	[*] P73112.	6,25	50	CLZ-FP-52/10	9	6.1 33	180x190x100	6,00
RZ-10-400	[*] P73115.	10	50	CLZ-FP-46/12,5	15	3.83 52	180x190x100	6,50
RZ-12,5-400	[*] P73117.	12,5	50	CLZ-FP-46/15	18	3.05 57	180x192x110	7,00
RZ-15-400	[*] P73120.	15	50	CLZ-FP-46/19	22	2.55 59	180x190x110	8,00
RBZ-20-400	[*] P73125.	20	50	CLZ-FP-46/25	29	1.91 79	235x165x125	14,00
RBZ-25-400	[*] P73130.	25	50	CLZ-FP-46/30	36	1.53 93	235x165x125	14,00
RBZ-30-400	[*] P73135.	30	50	2 x CLZ-FP-46/19	43	1.27 124	255x200x125	19,00
RBZ-40-400	[*] P73140.	40	50	2 x CLZ-FP-46/25	58	0.95 149	255x200x125	20,00
RBZ-50-400	[*] P73145.	50	50	2 x CLZ-FP-46/30	72	0.76 189	255x220x145	25,00
RBZ-60-400	[*] P73150.	60	50	3 x CLZ-FP-46/25	87	0.63 210	255x240x145	28,00
RBZ-80-400	[*] P73155.	80	50	3 x CLZ-FP-46/33,3	115	0.48 241	305x255x155	31,00
400 Vac, 50 Hz, f rezonancija = 134 Hz / p= 14%								
RZ-5-400-14%	[C] P731100000300	5	50	CLZ-FP-52/7,5-HD CFB-52/7,5	7,2	16.31 62	180x195x100	6,00
RZ-10-400-14%	[C] P731150000300	10	50	CLZ-FP-52/15-HD CFB-52/15	15	8.15 91	250x245x130	16,00
RZ-12,5-400-14%	[C] P731170000300	12,5	50	CLZ-FP-52/20-HD CFB-52/19	18	6.52 130	250x245x130	16,00
RZ-15-400-14%	[C] P731200000300	15	50	CLZ-FP-52/25-HD CFB-52/23	22	5.43 130	250x245x145	20,00
RZ-20-400-14%	[C] P731250000300	20	50	CLZ-FP-52/30-HD CFB-52/30	29	4.07 150	250x245x145	21,00
RBZ-25-400-14%	[C] P731300000300	25	50	CLZ-FP-52/12,5-HD + CLZ-FP-52/30-HD CFB-52/38	36	3.26 168	250x245x145	22,00
RBZ-30-400-14%	[C] P731350000300	30	50	CLZ-FP-52/25-HD + CLZ-FP-52/20-HD CFB-52/46	43	2.71 191	300x255x155	36,00
RBZ-40-400-14%	[C] P731400000300	40	50	2 x CLZ-FP-52/30-HD CFB-52/60,5	58	2.03 267	345x255x155	40,00
RBZ-50-400-14%	[C] P731450000300	50	50	3 x CLZ-FP-52/25-HD CFB-52/76	72	1.63 341	345x275x175	52,00
RBZ-60-400-14%	[C] P731500000300	60	50	3 x CLZ-FP-52/30-HD CFB-52/91	87	1.35 421	375x275x185	61,00



RZ-RBZ-60Hz

Reaktori III za detuniranje prigušnice, 60 Hz

Tip	Šifra	480 V kvar	Hz	Za kondenzator	L(mH)	težina (kg)
480 Vac, 60 Hz, f rezonancija = 227 Hz / p= 7%						
RZ-7,5-480-60 Hz-7%	[C] P731130017000	7,5	60	CLZ-FP-52/8,5-60Hz-HD	6,12	4,00
RZ-10-480-60Hz-7%	[C] P731150017000	10	60	CLZ-FP-52/11,5-60Hz-HD	4,58	5,00
RZ-12,5-480-60 Hz-7%	[C] P731170017000	12,5	60	CLZ-FP-52/15-60Hz-HD	3,66	6,00
RZ-15-480-60 Hz-7%	[C] P731200017000	15	60	CLZ-FP-52/17-60Hz-HD	3,06	7,00
RBZ-20-480-60Hz-7%	[C] P731250017000	20	60	CLZ-FP-52/22,5-60Hz-HD	2,29	15,00
RBZ-25-480-60 Hz-7%	[C] P731300017000	25	60	CLZ-FP-52/30-60Hz-HD	1,83	18,00
RBZ-30-480-60 Hz-7%	[C] P731350017000	30	60	CLZ-FP-52/34-60Hz-HD	1,53	18,00
RBZ-40-480-60Hz-7%	[C] P731400017000	40	60	2 x CLZ-FP-52/22,5-60Hz-HD	1,15	20,00
RBZ-50-480-60 Hz-7%	[C] P731450017000	50	60	2 x CLZ-FP-52/30-60Hz-HD	0,92	24,00
RBZ-60-480-60 Hz-7%	[C] P731500017000	60	60	2 x CLZ-FP-52/34-60Hz-HD	0,76	25,00
RBZ-80-480-60Hz-7%	[C] P731550017000	80	60	3 x CLZ-FP-52/30-60Hz-HD	0,58	35,00
480 Vac, 60 Hz, frezonancija= 160 Hz / p= 14%						
RZ-12,5-480-60Hz-14%	[C] P731170017300	12,5	60	CLZ-FP-60/17,5-60Hz-HD	7.81	16,00
RZ-15-480-60Hz-14%	[C] P731200017300	15	60	CLZ-FP-60/21-60Hz-HD	6.52	16,00
RBZ-25-480-60Hz-14%	[C] P731300017300	25	60	CLZ-FP-60/34,5-60Hz-HD	3.91	26,00
RBZ-30-480-60Hz-14%	[C] P731350017300	30	60	2 x CLZ-FP-60/21-60Hz-HD	3.26	41,00
RBZ-50-480-60Hz-14%	[C] P731450017300	50	60	2 x CLZ-FP-60/34,5-60Hz-HD	1.95	51,00

TABLICA DODATNIH ZNAČAJKI

RZ, RBZ										
P	7	X	X	X	X	0	0	X	X	X
Šifra						Interna šifra		↑	↑	↑
Frekvencija						Standard (50 Hz)		0	↑	↑
						60 Hz		1	↑	↑
						Standard (400 V _{c.a.})		0	↑	↑
Mapon						230 V _{c.a.}		1	↑	↑
						Ostali naponi		C	↑	↑
						Standard (7 %)		0	↑	↑
						5,67 %		4	↑	↑
Faktor P %						8,7 %		6	↑	↑
						14 %		3	↑	↑